

# \*\*\*\*\* INSTALLATION INSTRUCTIONS \*\*\*\*\*

## ASSEMBLY: ITEM NO. 40148

STEP1. TAKE OUT LAMP PARTS FROM THE PACKAGE SLOWLY, PLACE THEM ON SMOOTH AND LEVEL SURFACE.

STEP2. REMOVE THE VINYL DUST PROTECTED FILM FROM THE BODY AND THE SHADE.

STEP3. UNSCREW THE SOCKET RING FROM THE SOCKET.

STEP4. PUT THE SHADE BRACKET ONTO THE LAMP HOLDER, TIGHTEN IT BY THE SOCKET RING.

STEP5. ALIGN AND INSTALL THE BULB TO THE SOCKET.

STEP6. PUT THE SHADE ONTO THE SHADE BRACKET (THE SIDE WITH TWO SMALL EARS IS UNDER) LET THE UPPER PART OF THE SHADE BRACKET PROTRUDE INTO THE UPPER CIRCLE OF THE SHADE; HOLD THE TWO SMALL EARS AT THE BOTTOM OF THE LAMPSHADE AND STRETCH THE LAMPSHADE DOWNWARDS, UNTIL THE TWO SMALL EARS OF THE SHADE CAN BE HUNG ON THE LOWER BULGE OF THE SHADE BRACKET

### NOTICE:

IN THE PROCESS OF INSTALLATION AND USE, A SMALL AMOUNT OF FEATHERS DROP IS NORMAL, AND IT WILL NOT AFFECT THE NORMAL USE OF THE LAMP

