

REPORT

Technical Report: (8524)017-0201(Revised)

Page 1 of 28 January 27, 2024



Bureau Veritas Shenzhen Co., Ltd 1st Floor, Building 4, Hongchuang Science and Technology Center, Longhua District Shenzhen, Guangdong Province, China. Tel: 86-755-86185200 Fax: 86-755-86185206 www.bureauveritas.com/cps This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at https://www.bureauveritas.cn/SZ-SBUs-Terms-Conditions-EN and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by your negligence; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.











TEST REPORT

SHENZHEN

(8524)017-0201(Revised)

DONGGUAN MINGHAO INTELLIGENT HOME TECHNOLOGY CO LTD 27, ZHIWEI STREET, XIAOHE VILLAGE, DAOJIAO TOWN, DONGGUAN CITY

ATTN: / CC: /

DATE IN: MOD. LOG IN: DATE OUT: REVISED DATE: WORKING DAYS: PAGE:

LAB LOCATION:

LAB NUMBER:

January 18, 2024 / January 27, 2024 November 1, 2024 8 4 OF 28

OVERALL RATING

PASS FAIL DATA <u>x</u>

TESTING FOR ASTM F2057-2023 16 CFR 1303 LEAD CONTENT IN SURFACE COATING 40 CFR 770 EPA TSCA REQUIREMENTS CPSIA(LEAD AND PHTHALATE)

Sample Description:	WARD	RO	ЗE							
Manufacturer:	/				P.O. No.:	/				
Buyer:	/				Style:	/				
Country of Origin:	CHINA	۱.			Country of Destination:	AMER	RICA	١		
Color:	/				SKU Number:	ITEM#	# :			
						YG-5,	YG	-10, YG	15	
Appropriate Age	N/A (A	DUL	.T)		Tested Age Grade (if	ADUL	Т			
Grade (if applicable)					applicable)					
Re-test:	Yes:		No:	Х	Charge Vendor:	Yes:		No		Х
Previous Report No.:	/									



EXECUTIVE SUMMARY:

The submitted sample(s) meet all the test requirements. (PASS)

Evaluation Citation / Method		Criteria	Result	Rating
Clothing storage unit safety standard	16 CFR 1261 / ASTM F2057-23	Applicable to all free-standing clothing storage units, including but not limited to chests, chests of drawers, drawer chests, armoires, chifferobes, bureaus, door chests, and dressers, which are 27 in. (686 mm) or greater in height, 30 lb (13.6 kg) or greater in mass, and contain 3.2 ft3 (90.6 dm3) or greater of enclosed storage volume.	Μ	PASS
		Shall comply with ALL sections of ASTM F2057-23.		
Clothing storage unit safety standard	ASTM F2057-23 Section 4, Section 9	Shall comply with all performance requirements of ASTM F2057-23 when tested to section 4 and 9 with the unit set up in accordance with 8.1 of ASTM F2057-23.	Μ	PASS
Clothing storage unit safety standard	ASTM F2057-23 Section 10	Shall comply with all marking and labelling requirements of ASTM F2057-23	Μ	PASS
Clothing storage unit safety standard	ASTM F3096-23	Shall comply with all performance, labelling and instruction requirements of ASTM F3096-23	Μ	PASS
Clothing storage units - Anti-tip device – Presence	16 CFR 1261 / ASTM F2057-23 Sec 4.4	An anti-tip device shall be included with each item of furniture covered under the scope of this safety specification for attachment by the consumer.	Μ	PASS
Clothing storage units - Tipover restraints - Test method	16 CFR 1261 / ASTM F2057-23 Sec. 4.5 / ASTM F3096-23 Section 4	The tip over restraint shall withstand a force of 60 lb when tested to section 4 of ASTM F3096	Μ	PASS
Clothing storage units -	16 CFR 1261 / ASTM F2057-23	Installation instructions shall include at a minimum the following:	Μ	PASS
Tipover restraints -	Sec. 4.5 / ASTM F3096-23 Section	Illustration showing installation method.		
Installation	5.1	 Detailed written instructions with step-by- step instructions on how to properly attach the tipover restraint. 		
		Parts list including illustrations.		
Clothing storage units - Tipover restraints - installation instructions	16 CFR 1261 / ASTM F2057-23 Sec. 4.5 / ASTM F3096-23 Section 5.2	Clear and complete installation instructions for the tipover restraint shall be included.	М	PASS
Clothing storage units - Tipover	16 CFR 1261 / ASTM F2057-23 Sec. 4.5 / ASTM	The following information shall be provided with each tipover restraint:	Μ	PASS



Evaluation	Citation / Method	Criteria	Result	Rating
restraints - Labelling Requirements	F3096-23 Section 6	 Manufacturer's name and address. Date of manufacture (capable of identifying at a minimum the month and year of manufacture). 		
Clothing storage units - Interlock Requirement	16 CFR 1261 / ASTM F2057-23 Sec 4.6 & 9.1	Interlocks shall not require additional consumer action to engage during normal operation of the extendible element Interlocks shall not require consumer assembly and/or installation if the unit is shipped assembled, except as allowed in 4.6.1.1. Consumer assembly and/or installation of interlock components as part of the normal consumer assembly process is allowed for items shipped/sold unassembled. When tested to 9.1, the extendible element shall be considered interlocked to the open extendible element if either: (1) it remains closed during the test and is functional after tested extendible element is closed; or (2) its opening acts to close the extendible element originally open.	NA	/
Clothing storage units - Stability Test - Simulated Clothing Load	16 CFR 1261 / ASTM F2057-23 Sec 9.2.1/ASTM F2057-23 Sec 4.1,4.2,4.3	If 50% or more of the storage volume is extended, determine the weight for loading the extendable elements and/or space behind the doors based on the volume calculated in Section 5.4. Load per Section 8.3. 3 If less than 50% of the storage volume is extended, the unit shall remain empty. Open all doors and extend all available extendible elements in accordance with Section 8.1.3. Elements shall remain open for 30 s. The unit shall not top over during the test	Μ	PASS
Clothing storage units - Stability test - Simulated Horizontal Dynamic Force	16 CFR 1261 / ASTM F2057-23 Sec 9.2.2/Sec 4.1,4.2,4.3	Open all doors and all available extendable elements Apply 10 lbf (44 N) horizontal force, parallel to the direction of outward motion at the highest hand hold height, not to exceed 56 in on the extended element most likely to cause tip over This can be on an extendable element or door handle, whichever is highest, but not exceeding 56 in The unit shall not top over during the test	Μ	PASS
Clothing storage units - Stability test - Simulating a Reaction on Carpet with Child Weight:	16 CFR 1261 / 16 CFR 1261 / ASTM F2057-23 Sec 9.2.3/Sec 4.1,4.2,4.3	Place the Test block(s) under the unit's most rear floor support(s), such as a leg, foot or upright Open all doors and all available extendable elements Gradually, over period of 5 seconds, apply the	Μ	PASS



Evaluation	Citation / Method	Criteria	Result	Rating
		test apparatus with 60lb over the top of the door or extendable element most likely to cause tipover. Allow to rest without support for 30 seconds The unit shall not top over during the test NOTE: Conduct multiple tests if it is not clear which element is most likely to cause tip over		
Clothing storage units - Permanency of Labels and Warnings - Paper	16 CFR 1261 / ASTM F2057-23 Sec 9.3.1	A paper label shall be considered permanent if, during an attempt to remove it without the aid of tools or solvents, it cannot be removed, it tears into pieces upon removal, or such action damages the surface to which it is attached.	Μ	PASS
Clothing storage units - Permanency of Labels and Warnings – Non-Paper	16 CFR 1261 / ASTM F2057-23 Sec 9.3.2	A non-paper label shall be considered permanent if, during an attempt to remove it without the aid of tools or solvents, it cannot be removed or such action damages the surface to which it is attached.	NA	/
Clothing storage units - Permanency of Labels and Warnings – Applied Directly	16 CFR 1261 / ASTM F2057-23 Sec 9.3.3	The warning statements shall be considered permanent if the printing in the area tested per Method B – Cross-Cut Tape Test of Test Methods D3359 eliminating parallel cuts. is still legible and attached after being subjected to this test.	NA	/
Clothing storage units - Warnings on Product:	16 CFR 1261 / ASTM F2057-23 Sec 10.1	Each clothing storage unit shall be permanently marked in at least one place with the warnings from this section. The warnings shall be in a conspicuous location when in use. The warnings shall be applied on one surface, not wrapped or folded around or over corners.	Μ	PASS
Clothing storage units - Warnings Format and Content:	16 CFR 1261 / ASTM F2057-23 Sec 10.2	The warnings shall be formatted in a manner consistent with ANSI Z535.4. see below photo as an example. The contents of the warnings shall not be modified except as specifically indicated above and/or to include languages other than English. The warnings shall be permanent when tested in accordance with 9.3.1, 9.3.2, or 9.3.3 as appropriate.	Μ	PASS



Evaluation	Citation / Method	Criteria	Result	Rating
		A WAK NETG Children have died from furniture tipover. To reduce the rist of furniture bipover: -ALWAYS install Artific gavice provided. -NEVER put a TV on this product. -NEVER allow children to stand, climit or hang on drawers, doors, or shalves. -NEVER open more than one drawer at a time. -Place heaviest items in the lowest drawers. This is a permanent label. Do not rearing.		
16 CFR 1303 - Total Lead in Surface Coatings	16 CFR 1303 / Consumer Product Safety Improvement Act of 2008 / CPSC-CH- E1003-09.1	All accessible surface coatings, before and after use and abuse testing, on items intended for children ages 12 and under shall not contain lead or lead components in which the lead content is in excess of 0.009% (90ppm) of the weight of the total content. In case of insufficient coating for testing found on number of samples specified in the protocol, vendor needs to provide additional component parts (including raw materials) for testing. Report actual results or include data table within report. Issue a third party test report. Component testing is allowed. Based on CPSC SOP, will composite up to 3 colors. If any color in the composite exceeds 80% of the limit (72 ppm), based on the lowest weight component, individual colors will be analyzed	NA Non-Children Product	/
EPA TSCA title VI-Composite wood- Declaration form and mill certification	40 CFR 770	 If wood of any type is present in the sample, submitter shall provide a completed and signed Sample Declaration Form. Sections A, B, and E of the Sample Declaration Form must always be completed. If regulated composite wood is not present in the sample, result is N/A. If regulated composite wood is present in the sample: Section D of the Sample Declaration Form must also be completed Submitter shall provide a copy of the certificate issued by the Third Party Certifier (TPC) for the mill(s) from which the raw panels were purchased 	M Certificate was provided	PASS



Evaluation	Citation / Method	Criteria	Result	Rating
		be consistent with the Sample Declaration Form		
		Notes:		
		 Include a copy of the Sample Declaration Form in the report 		
		 Regulated composite wood includes: 		
		- Hardwood plywood (HWPW)		
		- Medium-density fiberboard (MDF)		
		- Thin medium-density fiberboard (Thin MDF)		
		- Particleboard (PB)		
		 Mill certificate must indicate compliance with TSCA Title VI. It is no longer acceptable to have the certificate indicate compliance with CARB's ATCM for formaldehyde in lieu of compliance with TSCA Title VI. 		
EPA TSCA Title VI–Composite wood-Finished good labeling	40 CFR 770.45(c) & (e)	Finished goods containing regulated composite wood shall comply with the labeling requirements found in 40 CFR 770.45(c) unless the finished good qualifies for the de minimis exception found in 40 CFR 770.45(e).	M Label was provided	PASS
		• A finished good does not require labeling per 40 CFR 770.45(c) if the finished good does qualify for the de minimis exception in 40 CFR 770.45(e). If the finished good does qualify for the de minimis exception, result is N/A.		
		A finished good does require labeling per 40 CFR 770.45(c) if the finished good does not qualify for the de minimis exeption in 40 CFR 770.45(e).		
		 At a minimum, the label must be on the product OR the packaging 		
		 The label may be applied as a stamp, tag, or sticker 		
		 The label shall include, at a minimum, in legible English text: 		
		1. Fabricator's name		
		Date the finished good was produced (in month/year format)		
		 A statement of compliance to denote that the finished good complies with TSCA Title VI 		



Evaluation	Citation / Method	Criteria	Result	Rating
Evaluation	Citation / Method	CriteriaExample: XXX Company MM/YYYY EPA TSCA Title VI compliant for formaldehydeNotes:•A de minimis amount of regulated composite wood is defined as regulated composite wood content not exceeding 144 square inches, based on the surface area of the largest face of the finished good.•The de minimis exception is not available to finished goods or component parts that are designed to be used in combination or in multiples to create larger surfaces,	Result	Rating
		 finished goods, or component parts. When a statement of compliance is necessary, the statement must denote that the finished good complies with TSCA Title VI. It is no longer acceptable to have the product labeled as compliant with CARB's ATCM for formaldehyde in lieu of a TSCA Title VI compliance statement. 		
Total lead in surface coating	16 CFR 1303 / Consumer Product Safety Improvement Act of 2008 / CPSC-CH- E1003-09.1	All accessible surface coatings in the assembled state on adult furniture [exempt factory applied coatings on metal components/parts] and household paint shall not contain lead or lead components in which the lead content is in exceed of 0.009% (90ppm) of the weight of the total content. In case of insufficient coating for testing found on number of samples specified in the protocol, vendor needs to provide dipped parts or components/parts for testing. Report actual results or include data table within report. Issue a program audit report. Component testing is allowed. Based on CPSC SOP, will composite up to 3 colors. If any color in the composite exceeds 80% of the limit (72 ppm), based on the lowest weight component, individual colors will be analyzed.	NA No surface coating	/
Total lead in substrate	Consumer Product Safety Improvement Act of	All accessible substrates, before and after use and abuse testing, on items intended for children ages 12 and under shall not contain	NA Non-Children Product	/



Evaluation	Citation / Method	Criteria	Result	Rating
	2008 / 16 CFR 1252 / CPSC-CH- E1001-08.3 / CPSC-CH-E1002- 08.3	 lead in excess of 0.01% (100ppm) of the weight of the total content. Note: In case of insufficient material for testing found on number of samples specified in the protocol, vendor needs to provide components/parts for testing. Report actual results or include data table within report. Issue a third party test report. Component testing is allowed. Compositing up to 3 like materials is allowed except metal. Exempt materials as defined by the Consumer Products Safety Commission in 16 CFR 1500.88, 16 CFR 1500.91 (d) and (e) and 16 CFR 1252 will not be tested. Untreated and unfinished engineered wood products (EWPs), specifically, particleboard, hardwood plywood, and medium-density fiberboard, made from virgin wood or preconsumer wood waste as defined in 16 CFR 1252 will not be tested. Vendor shall claim this determination in TRF, otherwise testing will be conducted in all woods. 		
Phthalates content	16 CFR 1307 / 16 CFR 1252 / CPSC- CH-C1001-09.4	Children's toys and childcare articles, before and after use and abuse testing, shall not contain concentrations of more than 0.1% BBP, DBP, DEHP, DINP, DIBP, DPENP(=DnPP), DHEXP(=DnHP) or DCHP individually. Actual testing would be conducted on all accessible plastics materials (including natural and synthetic rubber) (excluding materials listed below), plasticizer print, scrapable surface coatings, decals, polymeric coated materials (unscrapable), adhesives and sealants (exclude adhesive for stickers), polyvinyl acetate (PVAc) adhesive formulations used in hardwood plywood, toy nail polish, reusable packaging, electrical plug and cables. Polypropylene (PP), polyethylene (PE), acrylonitrile butadiene styrene (ABS), general purpose polystyrene (GPPS), medium-impact polystyrene (MIPS), high-impact polystyrene (HIPS), and super high-impact polystyrene	NA Non-Children Product	/



Evaluation	Citation / Method	Criteria	Result	Rating
		(SHIPS), and their additives as listed in 16 CFR 1308 are exempt from testing, however, they are not exempt from compliance or certification.		
		If material identification is not provided, phthalate testing will be conducted on all plastic materials. If adhesive formulation of hardwood plywood is not provided, phthalate testing will be conducted on all hardwood plywood.		
		Vendor shall be responsible for the compliance of all other accessible materials, including additives in the exempt plastic materials.		
		In case of insufficient material for testing found on number of samples specified in the protocol, vendor needs to provide components/parts for testing.		
		Report actual results or include data table within report.		
		Component testing is allowed.		
		Compositing up to 3 like materials is allowed.		

Enclosed storage volume specification

Evaluation	Data
Overall Height	74-1/4in
Overall weight	All>30lbs
Total Enclosed Storage Volume	A1: 17.42ft ³ , A2: 17.27ft ³ , A3: 42.8ft ³

REMARK(S):

- 1. As per client request, only the following test(s) was evaluated in this test report:
 - ASTM F2057-2023
 - 16 CFR 1303 lead content in surface coating
 - 40 CFR 770 EPA TSCA requirements
 - CPSIA(lead and phthalate)
- 2. No protocol is enclosed with this report.
- 3. (*)This report is amendment of and supersedes the previous (8524)017-0201 dated January 27,2024.



TOTAL LEAD CONTENT IN SURFACE COATING

Consumer Product Safety Improvement Act (CPSIA) of 2008"Ban of Lead-containing paint and certain consumer products bearing Lead-containing paint",(16 CFR 1303) Canadian Hazardous Products Act (CHPA), R.S., c. H-3, Schedule I, Part 1, Item 2

□ NO COMPOSITE ⊠ COMPOSITE

Element:		Lead				
Red	quirement: Maximum all	owable limit:				
	CHPA limit:			🗌 600 mg/kg		
CPSIA limit :		🖾 90 mg/kg				
	Sample	e Description		Result	Cond	clusion
	Color / Component	Location	Style	(mg/kg)	⊠CPSIA (90ppm)	CHPA (600ppm)
1	Black coating	Track of drawer handle	A1,A3, A3	<10	⊠PASS □FAIL	□PASS □FAIL

LT = Less Than

* = Average of duplicate analyses

mg/kg = milligrams per kilogram (ppm = parts per million) Detection Limit (ppm): 10

In some cases, the tested component cannot be tested individually due to overlapped coatings.

CPSIA Third Party Report (COULD/ COULDN'T/NO COMMENT) be issued.



NOTE: If there are questions or concerns regarding above report, please contact the appropriate lab persons.

Technical questions & concerns:

Keith Wang / Andy Fan (+86)755-32980234 / 32980214 Keith.wang@bureauveritas.com Andy.fan@bureauveritas.com

General Enquiries:

Rain Yuan / Coco Lee (+86)755-32980221 / 86135548 Rain.yuan@bureauveritas.com Coco.lee@bureauveritas.com

BUREAU VERITAS SHENZHEN CO., LTD

Sure Fu SENIOR TECHNICAL MANAGER HARDLINES DIVISION



Hardware pack

Manufacturer : Dongguan Minghao Intelligent Home Technology Co.Ltd Detailed address (including zip code) : No. 27, Zhiwei Street, Xiaohe Village, Daojiao Town, Dongguan City (523170) Manufacturing date : 2024-01



& WARNING	A MISE EN GARDE
Children have died from furniture tipover. To reduce the risk of furniture tipover: - ALWAYS install anti-tip device provided. - NEVER put a TV on this product - NEVER allow children to stand, climb or hang on any drawers, doors, or shelves. - NEVER open more than one drawer at a time. - Place heaviest items in the lowest drawer. This is a permanent label. Do not removel	Des enfants sont décèdes pour cause de renversement de meuble. Pour réduire la possibilité de renversement d'ameublement : • Installez TOUJOURS le dispositit anti- basculement fourni • Ne JAMAIS placer un téléviseur sur ce produit • Ne taissez JAMAIS les enfants se tenir debout, grimper ou s'accrocher à un tiroir, une porte ou une étagères. • N'ouvrez JAMAIS plus d'un firoir à la tois. • Placez les articles les plus lourds dans le firoir le plus bas. <i>Cet autocollant doit demeurer apposé</i>



EPA label

Manufacturer : Dongguan Minghao Intelligent Home Technology Co.Ltd

Detailed address (including zip code) : No. 27, Zhiwei Street, Xiaohe Village, Daojiao Town, Dongguan City (523170)

Manufacturing date : 23-01

EPA TSCA Title VI compliant for formaldehyde





(8524)017-0201(Revised) Page 19 of 28



Product Name:WARDROBE Model No:YG-5 Manufacturer: Dongguan Yingsheng Furniture Co., Ltd. Manufacturer Address: No.1 Zhenxing Road, Guanmeixla, Shuanggang, Houjie Town, Dongguan City, Guangdong Province, China Importer: TRANS-PAC CHINA LLC Importer address: 3715 S 182nd Street, C120 Seatac, WA98188-9993 US Te:+1(818)818-0538 Age of application: Over 18 years old Batch:AM-011 TPC#:TPC-48 Date of manufacture: MAY 17,2024 No. of Lot of Lo ATT DESCRIPTION

























100	COMPOSITE WOOD SAMPLE	CPSD-GB-08616.01-FORM		
	EPA TSCA TITLE VI	Version No.:	7	
VERITAS	CARB §93120 ATCM SOR/2021-148 FOR FORMALDEHYDE	Business Line:	GB	

Section A - Sample Information: This aection must be compl

Sample Description:

Item/SKU Number: YG-5, YG-15

Indicale if the sample is a

Panel

Finished Good

Section B - Federal regulations Section B1 - EPA TSCA Title VI Applicability:

Wardrobe

This section must be completed. The regulation can be viewed at: http://www.epa.gov/formaldehyde

- Composite wood is not present in the sample. If checked, proceed directly to Subsection B2.
- Composite wood is present in the sample and: \otimes If checked, indicate if regulated and/or exempt below. Then proceed to Subsection B2.

Regulated according to 40 CFR 770

cked, answer the following three questions and complete the shart in Section D

- 1. Indicate the type(s) of regulated composite wood (check all that apply);
 - Hardwood plywood veneer core (HWPW-VC) Hardwood plywood composite core (HWPW-CC)

 - Medium-density fiberboard (MDF)
- Thin medium-density fiberboard (Thin MDF)
- Particleboard (PB)
- 2. Indicate laminated product status under §770.4 (effective after March 22, 2024 for laminated portion):
- Sample is not a laminated product
- Sample is a laminated product and:
 - Laminated portion is not exempt from the definition of hardwood plywood per §770.4
 - Laminated portion is exempt from the definition of hardwood plywood per §770.4(a)(1)
 - Laminated portion is exempt from the definition of hardwood plywood per §770.4(a)(2)
- 3. For linished goods, indicate if labeling is present according to §770.45(c).

Sample is not a finished good

- Sample is a finished good and:
 - Labeling is not present
 - Labeling is not present and not required per §770.45(e)
 - Labeling is present

Exempt according to 40 CFR 770

- idicate the type(s) of exempt composite wood (check all that apply).
- Hardboard
- Oriented strand board
- Curved plywood

\$770.1(d) Windows that contain less than 5% by volume composite wood \$770.1(e)(1) Exterior doors and garage doors - (no added formaldehyde or ultra-low-emitting formaldehyde resin) §770.1(e)(2) Exterior doors and garage doors - (contains less than 3% by volume of composite wood)

Other List other type(s) of exempt composite wood and explain exemption:

Page 1 of 5



1		à	COMPOSITE WOOD SAMPLE	CPSD-GB-08616.01-F	
1		7		Version No.:	7
B	ERIT	AU	CARB §93120 ATCM SOR/2021-148 FOR FORMALDEHYDE	Business Line:	GB
eq his 48/	section section Full Te	tions	- Canada Formaldehyde Emissions from Composit s, SOR/2021-148 Applicability: st be completed: The regulation can be viewed at: https://laws-lois.justice. ol	e Wood Product	S OR-2021-
ichic arria	ate if ander	the sa	imple will be sold in Canada. If "No" is checked, proceed to section C. If " s section.	Yes" is checked, comple	ele lhe
	No				
	Yes				
	Com	nposit	te wood is not present in the sample.		
	er can	CUNCH	process stratuly to declary of		
	If chi	ecked.	e wood is present in the sample and: , indicate if regulated and/or exempt. Then proceed to Section C.		
		Reg If che	ulated according to SOR/2021-148 acked, answer the following three questions and complete the chart in Sec	ction D.	
		1. 11	idicate the type(s) of regulated composite wood (check all that apply):		
		C	Hardwood plywood (HWPW)		
			Particleboard (PB)		
		2	Medium-density fiberboard (MDF)		
		L	Thin medium-density fiberboard (Thin MDF)		
		2 11	idicate laminated product status under Section 33 (effective after January	7, 2028 for laminated p	ortion):
		Ē	Sample is not a laminated product Sample is a laminated product		
			a second second second and the second se		
		4	Sample is not a finished good		
		5	Sample is a finished good and		
			Labeling is not present		
			Labeling is not present and not required per Section 23		
			Labeling is present		
		Exe	mpt according to Section 4		
		Indic	ate the type(s) of exempt composite wood (check all that apply):		
		F	_ Hardboard		
		1	Curved alwood		
		F	Section 4(a) Windows that contain less than 5% by volume com	posite wood	
		F	Section 4(h) Exterior or parage doors that either contain less that	in 3% by volume com	nosite wo
	0	rism	ade with no-added formaldehyde or ultra-low-emitting-formaldehy	de resin	poone no
		Г	Other List other type(s) of exempt composite wood and explain exempt	tion:	



	(AL	COMPOSITE WOOD SAMPLE	CPSD-GB-08616.01	
2		DECLARATION FORM	Version No.:	7
6	ERITAS	CARB §93120 ATCM SOR/2021-148 FOR FORMALDEHYDE	Business Line:	GB
Se Se This woo	ction C - ction C1 s section mu od-products	State regulations: - CARB §93120 ATCM for Formaldehyde Applicabi st be completed. The regulation can be viewed at: https://ww2.arb.ca.o -prodram imple will be sold in California. If "No" is checked, proceed to Section D. I	lity: ov/our-work/programs f "Yes" is checked, comp	lcompos
em	ainder of this	s section.		
\times	Yes			
	Composit	e wood is not present in the sample.		
	Comment	proved in expect to the example and		
X	If checked	e wood is present in the sample and: indicate if regulated and/or exempt. Then proceed to Section D.		
	Reg	ulated according to the ATCM. acked, answer the following two questions and complete the chart in Sect	lion D.	
		Indicate the type(s) of regulated composite wood (check all that apply): Hardwood plywood – veneer core (HWPW-VC) Hardwood plywood – composite core (HWPW-CC) Medium-density fiberboard (MDF) Thin medium-density fiberboard (Thin MDF) Particleboard (PB)		
	2. F	or finished goods, indicate if labeling is present according to §93120.7(d)	5	
	L	Sample is not a finished good		
	L	Labeling is not present		
		⊠ Labeling is present		
	Exer	mpt according to the ATCM. ate the type(s) of exempt composite wood (check all that apply)		
] Hardboard		
	Ē	Curved plywood		
	Ē	§93120.7(b)(1) Windows that contain less than 5% by volume co	omposite wood	
	emittin	§93120.7(b)(2)(A) Exterior doors and garage doors – (no added g formaldehyde resin)	I formaldehyde or ultra	a-low-
	Compo	§93120.7(b)(2)(B) Exterior doors and garage doors – (contains site wood)	less than 3% by volum	ne of

Page 3 of 5



	COMPOSITE WOOD SAMPLE	CPSD-GB-08616.01-FORM		
	EDA TSCA TITLE VI	Version No.:	7	
VERITAS	CARB §93120 ATCM SOR/2021-148 FOR FORMALDEHYDE	Business Line:	GB	

Section D -Regulated Composite Wood Details:

site wood is present in the sample as declared in Subsections B1, B2, and/or Section C. Upon completion of this section. All fields in this section proceed to Section E must be con ad if regu

 $\label{eq:product} \begin{array}{l} \label{eq:product} Panel Types and Emission Limits Reference: \\ Hardwood plywood (HWPW) <math>\leq 0.05$ ppm Medium-density fibreboard (MDF) ≤ 0.11 ppm Thin medium-density fibreboard (MDF) ≤ 0.13 ppm Particleboard (PB) ≤ 0.09 ppm Laminated product ≤ 0.05 ppm

Examples of resin type include but are not limited to: • No-added formaldehyde-based (NAF) resin • Ultra low-emitting formaldehyde (ULEF) resin • Phenol-formaldehyde resin

Component of sample where composite wood is found:	Panel Type:	Emission Limit Met (ppm):	Resin Type:	Mill Name:	TPC Name:	TPC #:
(MDF) door plank	Back plate	≤ 0.13 ppm		Hezhou Sufeng Wood Co., Ltd.	ECC	ETEPAC N202300 02-TPC- -48

Page 4 of 5

(CA)	COMPOSITE WOOD SAMPLE	CPSD-GB-08616.	01-FORM
	EPA TSCA TITLE VI	Version No.:	7
VERITAS	CARB §93120 ATCM SOR/2021-148 FOR FORMALDEHYDE	Business Line:	GR

Section E – Declaration Signature: This section must be completed. Print name and provide a signature/ company chop.

.....

EPA TSCA Tifle VI / 40 CFR 770 is understood and if applicable, portions relevant to this sample have been met. Canada SOR/2021-148 is understood and if applicable, portions relevant to this sample have been met. CARB §33120 ATCM for Formatidshylo is understood and if applicable, portions relevant to this sample have been met. If a Third Party Certifier (TPC) is identified, it has been recognized by EPA and/or CARB. The required sections of this form have been completed accurately and truthfully.

Company Name:	Dengguan Yingsheng Furriture Co., Ltd.	
Company Address:	No. 1 Zhansing Road, Guannesnia, Shuanggang, Houjie Town, Dongguan City, Guangdong Province, China	
Date:	2024/5/17	
Name:	Yu Miao	
Title:		
Signature:		
	Canada Formaldehyde Emissions from Composite Wood Products Regulations, SOR/2021-148	

END OF REPORT